

VALTO | GLASBORD®



GLASBORD®

WALL PANELS WITH SURFASEAL FINISH

EMBOSSSED + SMOOTH TEXTURES



It's a dirty world out there. Protect your facility with Valto resilient wall coverings. Our GLASBORD with SURFASEAL® creates surfaces that deliver unsurpassed hygiene and durability for commercial environments such as restaurants and food processing plants.

Made of fiberglass reinforced plastic (FRP), GLASBORD with SURFASEAL is extremely moisture-resistant and non-porous. The SURFASEAL film finish, found only on GLASBORD, provides a barrier that's highly resistant to impact and scratching. Because of its unique process, the SURFASEAL finish will not trap soil or bacteria on the panel. The surface is up to 10 times easier to clean and up to six times more stain resistant than other sanitary wall systems. The sturdy panels, which come in both pebbled and smooth textures, hold up under frequent maintenance cycles, and proven performance at an affordable price point with a 10-year limited warranty.



**MOLD
RESISTANT**



**MEETS USDA/FSIS
REQUIREMENTS**



**EASY
INSTALL**



**EASY
CLEAN**



**DURABLE + IMPACT
RESISTANT**

WE HAVE TOUGH PANELS



FOR TOUGH ENVIRONMENTS

COLOR + FINISH OPTIONS

PEBBLED EMBOSSED TEXTURE



WHITE | 85



COLONIAL WHITE | 83



IVORY | 84



SOFT BEIGE | 70



SILVER | 66



PEARL GRAY | 48




SLATE GRAY | 1225




BLACK | 1201/97

SMOOTH TEXTURE



WHITE | 85




GRAY | 636



BLACK | 1201

DUE TO LIMITATIONS OF THE PRINTING PROCESS, PATTERNS AND COLORS MAY VARY. THEY ARE A REPRESENTATION OF THE PRODUCT. PLEASE OBTAIN A SAMPLE BEFORE MAKING A FINAL SELECTION AT FRPSAMPLES.COM

PRODUCT INFORMATION



AVAILABLE SIZES:

4' x 8' | 4' x 9' | 4' x 10' | 4' x 12' (other sizes available upon request)



THICKNESSES:

0.09" (embossed) | 0.075" (smooth)

FIRE RATINGS:

Class A or Class C per ASTM E-84
CAN/ULC-S102 | FM Approved Available

** see technical data sheets for fire rating information by color options



Now, a new way to apply FRP with our self-adhered frp wall panels!
glasbond.com



COMMERCIAL KITCHENS | FOOD PROCESSING PLANTS | RESTROOMS | CONVENIENCE STORES
LOCKER ROOMS | CLEANROOMS | CULTIVATION FACILITIES | COLD STORAGE




SEAM TREATMENT ACCESSORIES

Valto offers an array of seam treatment options to complete your wall panel installations.


PVC MOLDINGS

Standard moldings are contractor grade moldings that are perfect for use with FRP panels. Valto division bars feature patterned expansion control guides to assist with proper FRP installation. Available in 10' lengths in GLASBORD and KEMPLY standard colors.




COLORSIL COLOR-MATCHED CAULK

By Color Rite Inc., use for professional looking panel installations without the use of moldings. Valto has teamed up with Color Rite to provide materials that compliment Valto wall panels in over 40 colors. Use with Color Rite's Pre-Tooling Mist to install with ease.




POLYURETHANE SEAM SEALANT

Seam Sealant is an equal-mix, two-component bright white urethane sealant system used to bond and seal a variety of plastics.




STAINLESS TRIMS

Stainless steel trim pieces are the answer to having a sanitary, durable and clean transition while providing increased impact resistance and longevity to develop a more aesthetically pleasing finish.



SANI-BASE™

Use Sani-Base stainless accessories for innovative moisture mitigation solutions for seamless wall to floor transitions. Our Sani-Base accessories are available in five different profiles to fit your application needs.



FIRE-X GLASBORD (FXE and FFSM) is the only fiberglass reinforced interior wall and ceiling panel that is approved under FM Approvals Standard FM 4880 (Plastic Interior Finish Materials). Product installations should be in accordance with FM Approvals Standard FM 4880. This information is available at www.approvalguide.com and www.FRP.com/FMAproved.pdf.



GLASBORD panels are the first FRP panels that are HACCP certified. Hazard Analysis Critical Control Point (HACCP) certifies that GLASBORD panels are suitable for use in food and beverage facilities that operate in accordance with a HACCP based Food Safety Program. Orientation of embossed panels must be installed/ run vertically for any areas that require a sanitary finish under HACCP certification.



All Valto wall and ceiling coverings have earned GREENGUARD Certification for low chemical emissions, issued by UL Environment. This certification reflects our dedication to improving the quality of our products, while using low-emitting materials in their construction.



Thanks to their environmental benefits, the use of Valto products may also contribute to earning LEED® certification.



At Valto, we partner with our customers, and through innovation, we deliver advanced materials that enhance everyday environments. We succeed through a culture of collaboration, continuous improvement, and excellence. With integrity at our core, we challenge the status quo and pursue innovative approaches that benefit our customers and associates.

Since 1954, Valto Engineered Materials has provided innovative products and services and is a leading provider of FRP composite panels. Our lightweight composite products deliver unsurpassed strength and durability; and we continue to pioneer next level performance in building materials, recreational vehicles, and transportation.



VALTOfrp.com | 1.800.435.0080 | sales@valtoem.com

The following are trademarks of Valto, Inc. or a related company: Glasbord, Glasbond, Kemlite, Kemply, Surfaseal, Sanigrid, Silhouette Trims and Varietex
Form 6312 | Rev. 25 | 09.25 (10340)