

Safety Data Sheet

Issue Date: 28-Jun-2018

Revision Date: 02-Sept-2025

Version 1

1. IDENTIFICATION

Product Identifier

Product Name Color-Sil-Smooth

Other means of identification

SDS # CRI-009

Recommended use of the chemical and restrictions on use

Recommended Use Caulking compound. Sealant. Adhesive.

Details of the supplier of the safety data sheet

Supplier Address

Color Rite, Inc.
600 S. Ranchwood Boulevard
Yukon, Oklahoma 73009

Emergency Telephone Number

Company Phone Number 1-855-82CAULK
Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance According to product specification

Physical state Liquid

Classification

| | |
|-----------------------------------|------------|
| Skin corrosion/irritation | Category 2 |
| Serious eye damage/eye irritation | Category 2 |
| Reproductive toxicity | Category 2 |

Signal Word

Danger

Hazard statements

Causes skin irritation
Causes serious eye irritation
Suspected of damaging fertility or the unborn child



Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Wash face, hands and any exposed skin thoroughly after handling
Wear eye/face protection

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 IF ON SKIN: Wash with plenty of water and soap
 If skin irritation occurs: Get medical advice/attention
 Take off contaminated clothing and wash before reuse

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards

Harmful to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | CAS No. | Weight-% |
|--|------------|----------|
| Petroleum distillates, hydrotreated middle | 64742-46-7 | <30 |
| Ethyltriacetoxysilane | 17689-77-9 | <5 |
| Titanium(IV) Oxide | 13463-67-7 | <1 |
| Octamethylcyclotetrasiloxane | 556-67-2 | <1 |
| Cobalt titanite green spinel | 68186-85-6 | <1 |
| Carbon Black | 1333-86-4 | <1 |

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES**First Aid Measures**

General Advice Provide this SDS to medical personnel for treatment.

Eye Contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin Contact IF ON SKIN: Wash with plenty of water and soap. If skin irritation occurs: Get medical advice/attention.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Ingestion IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Seek medical attention.

Most important symptoms and effects

Symptoms Causes skin irritation. May include redness, drying and cracking of skin. Causes serious eye irritation. May cause discomfort if swallowed. Suspected of damaging fertility or the unborn child.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media Do not use heavy water stream or water jet stream as this may spread the fire.

Specific Hazards Arising from the Chemical

Not considered flammable, but will burn under fire conditions.

Hazardous Combustion Products Carbon oxides. Silicon oxides. Acetic acid. Formaldehyde.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

Personal Precautions Use personal protective equipment as required.

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up For waste disposal, see section 13 of the SDS.

7. HANDLING AND STORAGE**Precautions for safe handling**

Advice on Safe Handling Handle in accordance with good industrial hygiene and safety practice. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not eat, drink or smoke when using this product. Use personal protective equipment as required. Wear eye/face protection. Wash face, hands and any exposed skin thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed and store in a cool, dry and well-ventilated place. Protect from moisture. Keep container closed when not in use. Protect from direct sunlight. Protect from extreme temperatures. Store away from incompatible materials.

Incompatible Materials Strong acids. Strong bases. Strong oxidizers. Water.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|--|---|--|---|
| Colloidal silica 7631-86-9 | - | TWA: 50 µg/m ³ excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 6 mg/m ³ <1% Crystalline silica TWA: 20 mppcf : (80)/(% SiO ₂) mg/m ³ TWA | IDLH: 3000 mg/m ³ TWA: 6 mg/m ³ |
| Carbon Black 1333-86-4 | TWA: 3 mg/m ³ inhalable particulate matter | TWA: 3.5 mg/m ³ (vacated) TWA: 3.5 mg/m ³ | IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³ TWA: 0.1 mg/m ³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH |
| Titanium(IV) Oxide 13463-67-7 | TWA: 10 mg/m ³ | TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust | IDLH: 5000 mg/m ³ |
| Cobalt titanite green spinel 68186-85-6 | TWA: 0.02 mg/m ³ Co | - | IDLH: 10 mg/m ³ Ni TWA: 0.015 mg/m ³ except Nickel carbonyl Ni |

Appropriate engineering controls

| | |
|-----------------------------|---|
| Engineering Controls | Apply technical measures to comply with the occupational exposure limits. Showers. Eyewash stations. Ventilation systems. |
|-----------------------------|---|

Individual protection measures, such as personal protective equipment

Eye/Face Protection Chemical goggles or full face shield.

Skin and Body Protection Wear protective gloves and protective clothing.

Respiratory Protection Refer to 29 CFR 1910.134 for respiratory protection requirements.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| | | | |
|---------------------------------------|------------------------------------|-------------------------|----------------|
| Physical state | Liquid | | |
| Appearance | According to product specification | Odor | Not determined |
| Color | According to product specification | Odor Threshold | Not determined |
| Property | Values | Remarks • Method | |
| pH | Not determined | | |
| Melting point / freezing point | Not determined | | |
| Boiling Point / Boiling Range | Not determined | | |
| Flash Point | > 100 °C / 212 °F | | |
| Evaporation Rate | Not determined | | |
| Flammability (Solid, Gas) | Liquid- Not Applicable | | |
| Flammability Limit in Air | | | |
| Upper Flammability Limit | Not determined | | |
| Lower Flammability Limit | Not determined | | |
| Vapor Pressure | Not determined | | |
| Vapor Density | Not determined | | |
| Relative Density | Not determined | | |

| | |
|-------------------------------------|---------------------------|
| Water Solubility | Not determined |
| Solubility in other solvents | Not determined |
| Partition Coefficient | Not determined |
| Autoignition temperature | Not determined |
| Decomposition Temperature | Not determined |
| Kinematic Viscosity | Not determined |
| Dynamic Viscosity | 200,000 mPa.s (Estimated) |
| Explosive Properties | Not determined |
| Oxidizing Properties | Not determined |

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Avoid direct sunlight. Extreme temperatures. Avoid moisture. Ignition sources. Incompatible Materials.

Incompatible Materials

Strong acids. Strong bases. Strong oxidizers. Water.

Hazardous Decomposition Products

Carbon oxides. Silicone oxides. Acetic acid. Contact with water or humid air: Acetic acid
Thermal decomposition: Formaldehyde.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

| | |
|---------------------|--------------------------------|
| Eye Contact | Causes serious eye irritation. |
| Skin Contact | Causes skin irritation. |
| Inhalation | Do not inhale. |
| Ingestion | Do not ingest. |

Component Information

| Chemical Name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|--|-----------------------|-------------------------|-----------------------------------|
| Petroleum distillates, hydrotreated middle 64742-46-7 | = 7400 mg/kg (Rat) | > 2000 mg/kg (Rabbit) | = 4.6 mg/L (Rat) 4 h |
| Colloidal silica 7631-86-9 | = 7900 mg/kg (Rat) | > 2000 mg/kg (Rabbit) | > 2.2 mg/L (Rat) 1 h |
| Methyltriacetoxysilane 4253-34-3 | = 2060 mg/kg (Rat) | - | - |
| Octamethylcyclotetrasiloxane 556-67-2 | = 1540 mg/kg (Rat) | = 794 µL/kg (Rabbit) | = 36 g/m ³ (Rat) 4 h |
| Carbon Black 1333-86-4 | > 15400 mg/kg (Rat) | > 3 g/kg (Rabbit) | - |

| | | | |
|----------------------------------|-----------------------|---|---|
| Titanium(IV) Oxide 13463-67-7 | > 10000 mg/kg (Rat) | - | - |
|----------------------------------|-----------------------|---|---|

Information on physical, chemical and toxicological effects

Symptoms

Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen. However, the product as a whole has not been tested.

| Chemical Name | ACGIH | IARC | NTP | OSHA |
|--|-------|---------------------|---------------------------------|------|
| Colloidal silica 7631-86-9 | | Group 3 | Known | X |
| Carbon Black 1333-86-4 | A3 | Group 2B | | X |
| Titanium(IV) Oxide 13463-67-7 | | Group 2B | | X |
| Cobalt titanite green spinel 68186-85-6 | A3 | Group 2B Group 1 | Known Reasonably Anticipated | X |

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 IARC components are "not classifiable as human carcinogens"

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 9,550.00 mg/kg

ATEmix (dermal) 7,328.00 mg/kg

ATEmix (inhalation-gas) 2,565.00 mg/L

ATEmix (inhalation-vapor) 16.85 mg/L

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Component Information

| Chemical Name | Algae/aquatic plants | Fish | Crustacea |
|--|--|---|--|
| Petroleum distillates, hydrotreated middle 64742-46-7 | | 10000: 96 h Pimephales promelas mg/L LC50 static 35: 96 h Pimephales promelas mg/L LC50 flow-through | |
| Colloidal silica 7631-86-9 | 440: 72 h Pseudokirchneriella subcapitata mg/L EC50 | 5000: 96 h Brachydanio rerio mg/L LC50 static | 7600: 48 h Ceriodaphnia dubia mg/L EC50 |
| Octamethylcyclotetrasiloxane 556-67-2 | | 1000: 96 h Lepomis macrochirus mg/L LC50 500: 96 h Brachydanio rerio mg/L LC50 | 25.2: 24 h Daphnia magna mg/L EC50 |
| Carbon Black 1333-86-4 | | | 5600: 24 h Daphnia magna mg/L EC50 |

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

| Chemical Name | Partition Coefficient |
|--|-----------------------|
| Octamethylcyclotetrasiloxane 556-67-2 | 5.1 |

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS**Waste Treatment Methods****Disposal of Wastes**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

California Hazardous Waste Status

| Chemical Name | California Hazardous Waste Status |
|--|-----------------------------------|
| Cobalt titanite green spinel 68186-85-6 | Toxic |

14. TRANSPORT INFORMATION**Note**

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

Not regulated

IATA

Not regulated

IMDG**Marine Pollutant**

This material may meet the definition of a marine pollutant

15. REGULATORY INFORMATION**International Inventories**

| Chemical Name | TSCA | DSL/NDSL | EINECS/E LINCS | ENCS | IECSC | KECL | PICCS | AICS |
|--|------|----------|----------------|------|-------|------|-------|------|
| Petroleum distillates, hydrotreated middle | X | X | X | | X | X | X | X |
| Colloidal silica | X | X | X | X | X | X | X | X |
| Ethyltriacetoxysilane | X | X | X | X | X | X | X | X |
| Methyltriacetoxysilane | X | X | X | X | X | X | X | X |
| Octamethylcyclotetrasiloxane | X | X | X | X | X | X | X | X |
| Carbon Black | X | X | X | X | X | X | X | X |
| Titanium(IV) Oxide | X | X | X | X | X | X | X | X |
| Cobalt titanite green spinel | X | X | X | X | X | X | X | X |

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations**CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

| Chemical Name | CAS No. | Weight-% | SARA 313 - Threshold Values % |
|---|------------|----------|-------------------------------|
| Cobalt titanite green spinel - 68186-85-6 | 68186-85-6 | <1 | 1.0 0.1 |

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

| Chemical Name | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous Substances |
|------------------------------|-----------------------------|------------------------|---------------------------|----------------------------|
| Cobalt titanite green spinel | | X | | |

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals.

| Chemical Name | California Proposition 65 |
|---|---------------------------|
| Colloidal silica - 7631-86-9 | Carcinogen |
| Carbon Black - 1333-86-4 | Carcinogen |
| Titanium(IV) Oxide - 13463-67-7 | Carcinogen |
| Cobalt titanite green spinel - 68186-85-6 | Carcinogen |

U.S. State Right-to-Know Regulations

| Chemical Name | New Jersey | Massachusetts | Pennsylvania |
|--|------------|---------------|--------------|
| Colloidal silica 7631-86-9 | | X | X |
| Carbon Black 1333-86-4 | X | X | X |
| Titanium(IV) Oxide 13463-67-7 | X | X | X |
| Cobalt titanite green spinel 68186-85-6 | X | | X |

16. OTHER INFORMATION

| NFPA | Health Hazards | Flammability | Instability | Special Hazards |
|-------------|-----------------------|---------------------|-------------------------|----------------------------|
| HMIS | Not determined | Not determined | Not determined | Not determined |
| | Health Hazards | Flammability | Physical hazards | Personal Protection |
| | Not determined | Not determined | Not determined | Not determined |

Issue Date: 28-Jun-2018
Revision Date: 06-Jul-2018
Revision Note: New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet